Quassel IRC - Bug #322

"quasselcore -h|--help" tries to start quasselcore instead of just displaying the help message

09/21/2008 11:37 PM - billie

Status:	Resolved	**Start date:**	
Priority:	High	**Due date:**	
Assignee:	Sputnick	**% Done:**	0%
Category:	Quassel Core	**Estimated time:**	0.00 hour
Target version:	0.3.1		
Version:	0.13.1	**OS:**	Any

Description

The following is displayed after the help message.

quasselcore --help

2008-09-21 23:22:53 Info: Storage Backend is ready. Quassel Schema Version: 11
2008-09-21 23:22:53 Error: Could not open GUI client port 4242: The bound address is already in use

Just out of curiosity I tried to use a port which is not already used and I got the following.

quasselcore --port=3000 --help

2008-09-21 23:30:51 Info: Storage Backend is ready. Quassel Schema Version: 11
2008-09-21 23:30:51 Info: Listening for GUI clients on IPv6 port 3000 using protocol version 5

The strange thing is I can not find an additional process of quasselcore running at port 3000. So it is not really starting or dies immediately after issuing the command.

Associated revisions

Revision 0f4d21d538c8cb4c8fb12cd285c4d7556714c2f3 - 09/22/2008 05:40 PM - Manuel Nickschas

Don't start a core in CoreApplication's dtor... fixes BR #322

Revision 0f4d21d5 - 09/22/2008 05:40 PM - Manuel Nickschas

Don't start a core in CoreApplication's dtor... fixes BR #322

History

#1 - 09/22/2008 05:41 PM - Sputnick

http://git.quassel-irc.org/?p=quassel.git;a=commit;h=0f4d21d538c8cb4c8fb12cd285c4d7556714c2f3