

## Quassel IRC - Bug #517

### Real Name should be set from /etc/passwd

02/05/2009 05:46 PM - jussi01

<b>Status:</b>	Resolved	<b>Start date:</b>	02/05/2009
<b>Priority:</b>	Normal	<b>Due date:</b>	
<b>Assignee:</b>	Sputnick	<b>% Done:</b>	100%
<b>Category:</b>		<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	0.4.0	<b>OS:</b>	Linux
<b>Version:</b>	0.3.1+		
<b>Description</b>			
By proxy from IRC			
<Riddell> Sput: and why is the real name not set from /etc/passwd?			
<b>Related issues:</b>			
Related to Quassel IRC - Bug #516: Default Username should be users account name		<b>Resolved</b>	<b>02/05/2009</b>

#### Associated revisions

##### Revision ce6529a3ea1566d5d013f54608617e0c4fd982e0 - 02/11/2009 10:23 PM - Manuel Nickschas

Use GECOS field for real name on Unix, fixes #517

##### Revision ce6529a3 - 02/11/2009 10:23 PM - Manuel Nickschas

Use GECOS field for real name on Unix, fixes #517

#### History

##### #1 - 02/05/2009 08:03 PM - EgS

This should only apply in Mono mode.

If Quassel(core) is used as a service this could expose confidential data to the users.

##### #2 - 02/07/2009 04:59 PM - EgS

EgS wrote:

This should only apply in Mono mode.

If Quassel(core) is used as a service this could expose confidential data to the users.

This makes also sense in the Client only version, as we no longer create identities in the core.

##### #3 - 02/07/2009 05:01 PM - EgS

- % Done changed from 0 to 30

Using Mac OS CoreServices to chose a proper default real name

##### #4 - 02/07/2009 06:46 PM - EgS

- % Done changed from 30 to 70

Windows uses now GetUserName from the Advapi32 library

##### #5 - 02/11/2009 12:55 AM - Sputnick

- Status changed from New to Assigned

- Assignee set to Sputnick

- Target version set to 0.4.0

- OS set to Linux

**#6 - 02/11/2009 10:35 PM - Sputnik**

- Status changed from Assigned to Resolved

- % Done changed from 70 to 100

Applied in changeset [ce6529a3ea1566d5d013f54608617e0c4fd982e0](#).