

Quassel IRC - Bug #924

core segfaults on --add-user if it does not have permissions to the configdir

02/27/2010 10:21 PM - smithbone

Status:	Resolved	Start date:	02/27/2010
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Quassel Core	Estimated time:	0.00 hour
Target version:	0.6.0	OS:	Linux
Version:	0.5.0		

Description

On Ubuntu installs the configdir is in /var/cache/quassel and if an admin user does not have the required permissions to access the configdir then core will segfault.

100% repeatable for me and seen by others in the wild for both 0.5.0 and 0.5.1 using a PostgreSQL backend.

Short crash log:

Quassel IRC: 0.5.1 7cae1afb038d222d318da11c3bce23c9240eed0

```
1. 0 quasselcore 0x000000000550323 Quassel::logBacktrace(QString const&)
2. 1 quasselcore 0x000000000537e32 Quassel::handleSignal(int)
3. 2 libc.so.6 0x00007f07bc4330a0 0x0000000000000000
4. 3 quasselcore 0x00000000044a320 Core::createUser()
5. 4 quasselcore 0x000000000452bc8 Core::init()
6. 5 quasselcore 0x0000000004530c4 Core::instance()
7. 6 quasselcore 0x0000000004405ad CoreApplicationInternal::init()
8. 7 quasselcore 0x000000000440755 CoreApplication::init()
9. 8 quasselcore 0x00000000043ec38 main
10. 9 libc.so.6 0x00007f07bc41e466 __libc_start_main
11. 10 quasselcore 0x00000000043d869 0x0000000000000000
```

History

#1 - 03/04/2010 06:58 PM - johu

- Status changed from New to Resolved

- Target version set to 0.6.0